



twentieth

## Stickbulb Pendant

Stickbulb



### DESCRIPTION

Linear pendants are comprised of a central metal hardware component and two symmetrical bulbs. The overall length of the pendants can range from 4ft, 6ft, 8ft, 10ft, or 12ft. A clamping mechanism allows for the leveling of the bulbs. Bulbs can be oriented to provide down-light or uplight.

The wooden component is offered in sustainably sourced maple or walnut, reclaimed heart pine, ebonized oak, or reclaimed water tower redwood. The metal base is available in powder coated white, slate grey or matte black, hand blackened steel, polished nickel or brass, or brushed nickel or brass.

## ADDITIONAL INFORMATION

MATERIALS: LED, sustainably sourced or reclaimed wood, steel

FEATURES: Bulb direction reversible. Fully dimmable.

FIXTURE WEIGHT: 21.65 lbs / 9.8 kg

### FINISHES:

Wood: Maple, Walnut, Reclaimed Heart Pine, Reclaimed Water Tower Redwood, Ebonized Oak

Metal:

(Powder Coat): Matte White, Matte Slate Grey, Matte Black

(Premium): Blackened Steel, Polished Nickel, Brushed Brass

### DIMENSIONS:

Canopy: 7.5"L x 5.5"W x 1.5"D

Stem length: 6" - 72" available

DRIVER: Lutron 100%-1% driver included. 0-10V driver upon request.

### LIGHT SPECIFICATION

Standard Brightness LEDs: 794 Lumens / 94 CRI (3000K) / 40W Power draw

High Brightness LEDs: 1520 Lumens / 90 CRI (3000K) / 57W Power draw

COLOR TEMP: 2400k, 2700k, 3000k (Standard), 4000k

### INPUT VOLTAGE:

120V 50-60hz (Forward phase dimming)

120V-277V 50-60hz (3-wire dimming)

### LIGHT OUTPUT:

Standard Brightness - 12V (Dimmable)

High Brightness - 24V (Dimmable)

### STEM LENGTH:

60" length of 3/8" rigid steel stem. Additional stem length upon request at time of order.

CEILING: Flat Ceiling / Sloped Ceiling

---

**SPEC SHEET**