

twentieth

Stickbulb Multiple Pendant

Stickbulb



DESCRIPTION

Linear pendants can be grouped with three fixtures in a shared canopy. Each pendant is comprised of a central metal hardware component and two symmetrical bulbs.

The overall length of the pendants can range from 4ft, 6ft, 8ft, 10ft, or 12ft. A clamping mechanism allows for the leveling of the bulbs. Bulbs can be oriented to provide down-light or uplight.

The wooden component is offered in sustainably sourced maple or walnut, reclaimed southern yellow pine, or ebonized oak. Hardware is available in powder coated white, slate gray or matte black, hand blackened steel, polished nickel, and brushed brass.

ADDITIONAL INFORMATION

MATERIALS: LED, sustainably sourced or reclaimed wood, steel

FEATURES: Bulb direction reversible, fully dimmable

DIMENSIONS:

Canopy: 7.5"L x 5.5"W x 1.5"D

Stem Length: 6" - 72" available

Pendant Length: 4ft, 6ft, 8ft, 10ft, 12ft

FINISHES:

Wood: Maple, American Walnut, Ebonized Oak, Heart Pine (Reclaimed), Water Tower Redwood (Reclaimed), Custom

Metal:

(Powder Coat) - White, Slate Grey, Matte Black

(Premium Finish) - Hand Blackened Steel, Brushed Nickel, Polished Nickel, Brushed Brass, Polished Brass, Custom

VOLTAGE: 120V 50-60hz or 277V 50-60hz options available

DRIVER: built-in forward phase dimming driver 100%-1% (compatible with triac 2-wire dimmers with neutral connection)

COLOR TEMP: 2400k, 2700k, 3000k (Standard), 4000k

INPUT VOLTAGE: 120V 50-60hz (Forward phase dimming), 120V-277V 50-60hz (3-wire dimming)

LIGHT OUTPUT: Standard Brightness - 12V (Dimmable), High Brightness - 24V (Dimmable)

STEM LENGTH: 60" length of 3/8" rigid steel stem. Additional stem length upon request at time of order.

CEILING: Flat Ceiling, Sloped Ceiling

SPEC SHEET