



DESCRIPTION

44 SERIES

Each 44 results from a free pour of molten aluminum into a large canister filled with rock-like modules of resin-impregnated sand, a waste product of conventional sand casting. Low voltage electricity is transmitted through the castings, allowing a light source to be suspended between them without using cables.

CATALOG

ADDITIONAL INFORMATION

SIZE

44.3m: Three pendant fixture
44.3: Three pendant fixture
44.8: Eight pendant fixture
44.14: Fourteen pendant fixture

DIMENSIONS

Pendant: Ø 7.9 "

MATERIALS

Cast Aluminum, Braided Metal Coaxial Cable, Aircraft Cable, Electrical Components, White Powder Coated Canopy

CONNECTION + DROP

(10') standard - (35') maximum
Adjustable: 44.3 - 44.14

LAMPING

1.5w LED: 2000K, 2500K or 3500K

CANOPY

Brushed nickel, Black powder, or White powder coated adjustable lengths canopy: 44.3m, 44.8, 44.14
44.3m - 2.4" Ø x .25" round canopy
44.3 - 7.9" Ø x 1.25" round canopy
44.8 - 33.46" x 11.18" rectangular canopy
44.14 - 33.46" x 11.18" rectangular canopy

CUSTOM

Available

SPEC SHEETS	VIEW BOOK	INSTALL GUIDES	TABLE LIGHT 3D FILES .ZIP	RANDOM 3D FILES
.ZIP				