

ORDER CONFIRMATION FORM

ABACUS SERIES

Please fill out this form for each fixture on order

Project Name / Side Mark: _____ PO # _____ Invoice # _____

FIXTURE	SIZE		TOTAL DROP (Please provide total height, from ceiling to base of fixture) MM
	IMPERIAL	METRIC	
<input type="checkbox"/> Abacus	<input type="checkbox"/> 900 x 65 x 340 mm	35.4 x 2.6 x 13.4 "
	<input type="checkbox"/> 1200 x 65 x 340 mm	47.2 x 2.6 x 13.4 "	
	<input type="checkbox"/> 1500 x 65 x 340 mm	59.0 x 2.6 x 13.4 "	
	<input type="checkbox"/> 1800 x 65 x 340 mm	70.9 x 2.6 x 13.4 "	
	<input type="checkbox"/> 2100 x 65 x 340 mm	82.7 x 2.6 x 13.4 "	
	<input type="checkbox"/> 2400 x 65 x 340 mm	94.5 x 2.6 x 13.4 "	

Additional Quartz Drop
Quantity

SURFACE FINISH	LED COLOUR TEMPERATURE
<input type="checkbox"/> Aged Brass AB	<input type="checkbox"/> WARM WHITE 2500 - 2700K
<input type="checkbox"/> Custom	<input type="checkbox"/> NEUTRAL WHITE 3000 - 3300K

CEILING CANOPY (Please refer to Canopy Specification Guide provided)

LINEAR ABACUS CANOPY - FLUSH ABA.LF

LINEAR ABACUS CANOPY - SURFACE ABA.LS

Other

DIMMING (Please refer to Dimming Fact Sheet and Wiring Diagrams provided)

0-10V 4 wire dimming (additional control cables from dimming module to control required)

DALI/DSI 4 wire dimming (additional control cables from dimming module to control required)

REMOTE Lutron Powpak + Pico RF Remote Dimming Module (Stand Alone)

N/A Dimming Modules not required

SPECIFIC CERTIFICATION REQUIREMENTS

Y Please specify

N