



AERIS

PENDANT

Inspired by the ethereal beauty of clouds, Aeris embodies softness and lightness through the repetition of sculptural forms, crafting an ethereal centerpiece. Each mouth blown glass cloud is paired with architecturally crafted brass bars that cross and lightly kiss together, evoking a sense of weightlessness—as if suspended in air.

The duality of the brass structural element defines each piece, with dual vertical drops playfully interacting with horizontal crossings, creating a unity to the entire fixture.

AVAILABLE FINISHES




TECHNICAL

MATERIAL	TREATED BRASS, GLASS
FINISH	ALL BRASS FRAMES ARE BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) 8W, 2700K WATTAGE AND LUMEN OUTPUT WILL VARY SLIGHTLY DEPENDING ON CONSTANT CURRENT OUTPUT. LUMEN OUTPUT PER SHADE CLEAR - 440LM WHITE - 430LM BLACK - 230LM FROSTED BLACK - 130LM
DIMMING	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100% 110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100% ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.
LED LIFESPAN	50,000 HRS
IP RATING	IP20 - FOR INDOOR USE ONLY
CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN UL1598, CSA C22.2#250.0
CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE

DRIVER SIZE	220-240V PHASE L101 X W49 X H29 / L4" X W2" X H1.1" 220-240V DALI L145 X W30 X H21 / L5.7" X W1.2" / X H0.9" 110-120V TRIAC *L75 X W35 X H26.5 / L3" X W1.4" X H1" 110-120V DALI *L75 X W35 X H26.5 / L3" X W1.4" X H1" *DRIVER CAN BE HOUSED WITHIN STANDARD 4" OCTAGONAL JUNCTION BOX.
SKU CODES	EG. AEP.G-WHT.BR-BRZ AERIS PENDANT IN WHITE GLASS WITH A BRUSHED BRONZED BRASS FRAME AE104.G-XXX.BR-XXX GLASS FROSTED BLACK (G-FBL) BLACK (G-BLK) WHITE (G-WHT) CLEAR (G-CLR) FRAME BRUSHED BRASS (BR-NAT) BRUSHED BLACKENED BRASS (BR-BLK) BRUSHED BRONZED BRASS (BR-BRZ)
PRODUCT WEIGHT	4KG / 8.8LB
PACKAGE WEIGHT	5KG / 11LB
PACKAGE SIZE	1 X L 620 W 320 H 320 / L 24.4" W 12.6" H 12.6"

DIMENSIONS



L 245 W 245 H 155
L 9.6" W 9.6" H 6.1"
MIN DROP HEIGHT - H 400 / 15.7"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE SLIM CANOPY WILL BE SUPPLIED.



SLIM
Ø14MM DOUBLE CANOPY
CAN.SL.F14.XX-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING



PUCK
Ø14MM DOUBLE CANOPY
CAN.PK.D14.XX-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE INSTALLED WITH SUPPLIED JUNCTION BOX RENDER MOUNTING PLATE



LARGE
Ø14MM DOUBLE CANOPY
CAN.ST.170.F14.XX-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY

*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION, , TOLERANCE IS +/- 25MM
*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.