



AERIS

PENDANT

Inspired by the ethereal beauty of clouds, Aeris embodies softness and lightness through the repetition of sculptural forms, crafting an ethereal centerpiece. Each mouth blown glass cloud is paired with architecturally crafted brass bars that cross and lightly kiss together, evoking a sense of weightlessness—as if suspended in air.

The duality of the brass structural element defines each piece, with dual vertical drops playfully interacting with horizontal crossings, creating a unity to the entire fixture.


AVAILABLE FINISHES



TECHNICAL

MATERIAL	TREATED BRASS, GLASS	CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 UL1598, CSA C22.2#250.0
FINISH	ALL BRASS FRAMES ARE BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.	CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE	
LAMPING	FIXED TEMP - 2700K 8W, SELV 60V (EXTERNAL DRIVER SUPPLIED) DIM TO WARM - 1800-3000K 10W, SELV 60V (EXTERNAL DRIVER SUPPLIED) WATTAGE AND LUMEN OUTPUT WILL VARY SLIGHTLY DEPENDING ON CONSTANT CURRENT OUTPUT.	DRIVER SIZE 220-240V PHASE 220-240V DALI 110-120V PHASE 110-120V DALI	L101 X W49 X H29 / L4" X W2" X H1.1" L145 X W30 X H21 / L5.7" X W1.2" / X H0.9" *L75 X W35 X H26.5 / L3" X W1.4" X H1" *L75 X W35 X H26.5 / L3" X W1.4" X H1" *DRIVER CAN BE HOUSED WITHIN STANDARD 4" OCTAGONAL JUNCTION BOX.	
DIMMING	LUMEN OUTPUT PER SHADE CLEAR - 1000LM BLACK - 900LM 220-240V REGION PHASE DALI 110-120V REGION PHASE DALI ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	SKU CODES EG. AEP.G-WHT.BR-BRZ AERIS PENDANT IN WHITE GLASS WITH A BRUSHED BRONZED BRASS FRAME AE104.G-XXX.BR-XXX GLASS FROSTED BLACK (G-FBL) BLACK (G-BLK) WHITE (G-WHT) CLEAR (G-CLR) FRAME BRUSHED BRASS (BR-NAT) BRUSHED BLACKENED BRASS (BR-BLK) BRUSHED BRONZED BRASS (BR-BRZ)		
LED LIFESPAN	50,000 HRS	PRODUCT WEIGHT	4KG / 8.8LB	
IP RATING	IP20 - FOR INDOOR USE ONLY	PACKAGE WEIGHT	5KG / 11LB	
		PACKAGE SIZE	1 X L 620 W 320 H 320 / L 24.4" W 12.6" H 12.6"	

DIMENSIONS



L 245 W 245 H 155
L 9.6" W 9.6" H 6.1"
MIN DROP HEIGHT - H 400 / 15.7"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE SLIM CANOPY WILL BE SUPPLIED.



SLIM
Ø14MM DOUBLE CANOPY
CAN.SL.F14.XX-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING



PUCK
Ø14MM DOUBLE CANOPY
CAN.PK.D14.XX-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE
INSTALLED WITH SUPPLIED
JUNCTION BOX RENDER
MOUNTING PLATE



LARGE
Ø14MM DOUBLE CANOPY
CAN.ST.170.F14.XX-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY

TECHNICAL

MATERIAL	TREATED BRASS
	 BRUSHED BRASS  BRUSHED BLACKENED BRASS  BRUSHED BRONZED BRASS
CANOPY FINISH	BRUSHED BRASS (BR-NAT) BRUSHED BLACKENED BRASS (BR-BLK) BRUSHED BRONZED BRASS (BR-BRZ)
SKU CODES	EG. CAN.SL.D14.BR-BLK = SLIM DOUBLE CANOPY IN BRUSHED BLACKENED BRASS FINISH

*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION, , TOLERANCE IS +/- 25MM
*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.