



SOLACE

PENDANT

Solace is a luminous glass tear that transforms with movement, revealing two distinct identities in light and form. Through the exploration of geometric form the interplay of two perpendicular, intersecting circles serve as the foundation for this intricate composition.

Visually enchanting, Solace emerges from a series of experiments that use innovative engineering and push the boundaries of traditional glassblowing techniques.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	TREATED BRASS, GLASS	CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE
FINISH	ALL BRASS COMPONENTRY IS BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.	DRIVER SIZE	220 -240V PHASE L101 X W51 X H29 / L4" X W2" X H1.1" 220-240V DALI L145 X W30 X H21 / L5.7" X W1.2" / X H0.9" 110-120V TRIAC *L75 X W35 X H26.5 / L3" X W1.4" X H1" 110-120V DALI *L75 X W35 X H26.5 / L3" X W1.4" X H1"
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) 8W, 2700K	LUMEN OUTPUT BASED ON FINISH	WHITE - 700LM FROSTED CLEAR - 700LM FROSTED BLACK - 500LM
DIMMING	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100% 110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100%	SKU CODES	EG. SOP.G-FCL.BR-BLK SOLACE PENDANT IN FROSTED CLEAR GLASS WITH A BRUSHED BLACKENED BRASS BODY SOL.G-XXX.BR-XXX GLASS FROSTED BLACK (G-FBL) FROSTED CLEAR (G-FCL) WHITE (G-WHT) BODY BRUSHED BRASS (BR-NAT) BRUSHED BLACKENED BRASS (BR-BLK) BRUSHED BRONZED BRASS (BR-BRZ)
LED LIFESPAN	50,000 HRS	PRODUCT WEIGHT	6KG / 13.2LB
IP RATING	IP20 - FOR INDOOR USE ONLY	PACKAGE WEIGHT	7KG / 15.5LB
CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN UL1598, CSA C22.2#250.0	PACKAGE SIZE	L 360 W 360 H 550 / L 26" W 26" H 34"
	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.		
	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.		

DIMENSIONS



L 195 W 195 H 370
L 7.7" W 7.7" H 14.6"
MIN DROP HEIGHT - H 850 / 33.5"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE SLIM CANOPY WILL BE SUPPLIED.



SLIM
Ø14MM FIXED CANOPY
CAN.SL.F14.XX-XXX
Ø120 X 7MM / 4.7" X 0.3"
DRIVER HOUSED IN CEILING



SLIM
Ø14MM FIXED SWIVEL CANOPY
CAN.SL.F14.SW.XX-XXX
Ø120 X 7MM / 4.7" X 0.3"
DRIVER HOUSED IN CEILING



PUCK*
Ø14MM FIXED CANOPY
CAN.PK.F14.XX-XXX
Ø50 X 65MM / 2" X 2.6"
DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE INSTALLED WITH SUPPLIED JUNCTION BOX RENDER MOUNTING PLATE



PUCK*
Ø14MM FIXED SWIVEL CANOPY
CAN.PK.F14.SW.XX-XXX
Ø50 X 65MM / 2" X 2.6"
DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE INSTALLED WITH SUPPLIED JUNCTION BOX RENDER MOUNTING PLATE



LARGE
Ø14MM FIXED CANOPY
CAN.ST.170.F14.XX-XXX
Ø170 X 40MM / 6.7" X 1.6"
DRIVER HOUSED IN CANOPY



LARGE
Ø14MM FIXED SWIVEL CANOPY
CAN.ST.170.F14.SW.XX-XXX
Ø170 X 40MM / 6.7" X 1.6"
DRIVER HOUSED IN CANOPY

*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION, TOLERANCE IS +/- 25MM
*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.