



SOLACE

PENDANT

Solace is a luminous glass tear that transforms with movement, revealing two distinct identities in light and form. Through the exploration of geometric form the interplay of two perpendicular, intersecting circles serve as the foundation for this intricate composition.

Visually enchanting, Solace emerges from a series of experiments that use innovative engineering and push the boundaries of traditional glassblowing techniques.


AVAILABLE FINISHES



TECHNICAL

MATERIAL	TREATED BRASS, GLASS	CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 UL1598, CSA C22.2#250.0
FINISH	ALL BRASS COMPONENTRY IS BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.	CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE	
LAMPING	FIXED TEMP - 2700K 8W, SELV 60V (EXTERNAL DRIVER SUPPLIED) DIM TO WARM - 1800-3000K 10W, SELV 60V (EXTERNAL DRIVER SUPPLIED) LUMEN OUTPUT BASED ON FINISH WHITE - 700LM FROSTED CLEAR - 700LM FROSTED BLACK - 500LM BLACK - 900LM	DRIVER SIZE	220-240V PHASE - L101 X W51 X H29 / L4" X W2" X H1.1" 220-240V DALI - L145 X W30 X H21 / L5.7" X W1.2"/ X H0.9" 110-120V PHASE - *L75 X W35 X H26.5 / L3" X W1.4" X H1" 110-120V DALI - *L75 X W35 X H26.5 / L3" X W1.4" X H1" *DRIVER CAN BE HOUSED WITHIN STANDARD 4" OCTAGONAL JUNCTION BOX.	
DIMMING	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100% 110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100% ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	SKU CODES	EG. SOP:G-FCL:BR-BLK SOLACE PENDANT IN FROSTED CLEAR GLASS WITH A BRUSHED BLACKENED BRASS BODY GLASS FROSTED BLACK (G-FBL) FROSTED CLEAR (G-FCL) WHITE (G-WHT) BLACK (G-BLK) BODY BRUSHED BRASS (BR-NAT) BRUSHED BLACKENED BRASS (BR-BLK) BRUSHED BRONZED BRASS (BR-BRZ)	
LED LIFESPAN	50,000 HRS	PRODUCT WEIGHT	6KG / 13.2LB	
IP RATING	IP20 - FOR INDOOR USE ONLY	PACKAGE WEIGHT	7KG / 15.5LB	
		PACKAGE SIZE	L 360 W 360 H 550 / L 26" W 26" H 34"	

DIMENSIONS



L 195 W 195 H 370
L 7.7" W 7.7" H 14.6"
MIN DROP HEIGHT - H 850 / 33.5"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE SLIM CANOPY WILL BE SUPPLIED (OR LARGE FOR US/CAN REGIONS). CANOPY FINISH TO MATCH BODY, UNLESS OTHERWISE SPECIFIED.



SLIM
Ø14MM FIXED CANOPY
CAN.SL.F14.XX-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING



SLIM
Ø14MM FIXED SWIVEL CANOPY
CAN.SL.F14.SW.XX-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING



PUCK*
Ø14MM FIXED CANOPY
CAN.PK.F14.XX-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE
INSTALLED WITH SUPPLIED
JUNCTION BOX RENDER
MOUNTING PLATE



PUCK*
Ø14MM FIXED SWIVEL CANOPY
CAN.PK.F14.SW.XX-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE
INSTALLED WITH SUPPLIED
JUNCTION BOX RENDER
MOUNTING PLATE



LARGE
Ø14MM FIXED CANOPY
CAN.ST.170.F14.XX-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY



LARGE
Ø14MM FIXED SWIVEL CANOPY
CAN.ST.170.F14.SW.XX-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY

TECHNICAL

MATERIAL	TREATED BRASS
	 BRUSHED BRASS  BRUSHED BLACKENED BRASS  BRUSHED BRONZED BRASS
CANOPY FINISH	BRUSHED BRASS (BR-NAT) BRUSHED BLACKENED BRASS (BR-BLK) BRUSHED BRONZED BRASS (BR-BRZ)
SKU CODES	EG. CAN.SL.F14.BR-BLK = SLIM FIXED CANOPY IN BRUSHED BLACKENED BRASS FINISH

*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION, TOLERANCE IS +/- 25MM
*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.