



VOLANT

WALL LIGHT

Volant features solid brass bars, paired with textured, tubular formed-glass elements, creating a statement luminaire. This delicate light creates an equilibrium between the different materials and offers a beautifully soft level of luminosity.

Volant’s architectural nature allow the fixture to span across a plethora of interior spaces. The solid brass bars are individually machined with the luminaire defined by a white glass diffuser which is pinned in-place to the solid brass bar. Textured tubular glass elements are balanced on the same pins creating a uniquely formed illumination.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	TREATED BRASS, GLASS		IP RATING	IP20 - FOR INDOOR USE ONLY	
FINISH	ALL BRASS FRAMES ARE BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.		CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 UL1598, CSA C22.2#250.0
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) VW1 - 5.3W, 2700K VW2 - 7.8W, 2700K		WALL MOUNT DIMENSIONS	VW1 - H 330 X W 22 / H 13" X W 0.9" VW2 - H 330 X W 15.5 / H 13" X W 0.6"	
DIMMING OPTIONS	LUMEN OUTPUT PER SHADE CLEAR FLUTED - 650LM FROSTED FLUTED - 450LM FROSTED BLACK - 150LM FROSTED WHITE - 400LM			US / CAN MOUNTING OPTION 1 – JUNCTION BOX COVER PLATE FITS STANDARD 4" OCTAGONAL JUNCTION BOXES. INCLUDES COVER PLATE (H 9.9" × W 4.7" X D 0.2") AND A MOUNTING PLATE.	
	220-240V REGION PHASE - DIMMING RANGE 5 - 100% DALI - DIMMING RANGE 1 - 100%			OPTION 2 – JUNCTION BOX RENDER PLATE RENDER PLATE MOUNTED DIRECTLY TO JUNCTION BOX AND PATCHED AND PAINTED OVER.	
	110-120V REGION PHASE - DIMMING RANGE 3 - 100% DALI - DIMMING RANGE 0.1 - 100%			EITHER OPTION SUPPLIED ONLY FOR US/CANADA ONLY. CONTACT STUDIO FOR FURTHER DETAILS.	
	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.		SKU CODES	EG. VW2.G-CFL.BR-BRZ VOLANT DOUBLE WALL LIGHT IN CLEAR FLUTED GLASS WITH A BRUSHED BRONZED BRASS FRAME	
	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.			VW1.G-XXX.BR-XXX VW2.G-XXX.BR-XXX	VOLANT SINGLE WALL LIGHT VOLANT DOUBLE WALL LIGHT
DRIVER SIZE 220 -240V	PHASE ALL VW	- L101 X W51 X H29 / L4" X W2" X H1.1"	FINISHES GLASS	FROSTED BLACK (G-FBL) FROSTED FLUTED (G-FFL)	CLEAR FLUTED (G-CFL) FROSTED WHITE (G-FWH)
	DALI ALL VW	- L120 X W51 X H29 / L4.7" X W2" X H1.1"	FRAME	BRUSHED BRASS (BR-NAT) BRUSHED BLACKENED BRASS (BR-BLK) BRUSHED BRONZED BRASS (BR-BRZ)	
110-120V	PHASE ALL VW	- L75 X W35 X H26.5 / L3" X W1.4" X H1"	PRODUCT WEIGHT	VW1 VW2	2KG / 4.4LB 5KG / 11LB
	DALI ALL VW	- L88 X W43 X H26.5 / L3.5" X W1.7" X H1"	PACKAGING WEIGHT	VW1 VW2	1 X 3KG / 6.6LB 1 X 6KG / 13.2LB
LED LIFESPAN	50,000 HRS		PACKAGING SIZE	VW1 VW2	L 550 W 260 H 100 / L 21.6" W 10.3" H 4" L 550 W 340 H 100 / L 21.6" W 10.3" H 4"

DIMENSIONS



VW1
W 70 H 500 D 80
W 2.8" H 19.7" D 3.2"

*DOTTED LINE REPRESENTS
OPTIONAL US/CAN JUNCTION BOX
COVER PLATE



VW2
W 160 H 500 D 80
W 6.3" H 19.7" D 3.2"

*DOTTED LINE REPRESENTS
OPTIONAL US/CAN JUNCTION BOX
COVER PLATE