



LIMINAL

LINEAR PENDANT

Liminal exists in the threshold between object and space. Its floating silhouette is suspended by a trio of central support rods, creating a carefully balanced composition unique to the piece.

Offering independently switched uplight and downlight illumination, Liminal allows for layered atmospheric control within a single fixture. A modular lap joint detail defines the fixture’s side profile, reinforcing its architectural character. Available in five lengths and eleven standard finishes, Liminal adapts seamlessly across a range of architectural environments while maintaining its quiet, immersive presence.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	TREATED BRASS OR TREATED / ANODISED ALUMINIUM	
LAMPING	2700K, SELV 60V (EXTERNAL DRIVER SUPPLIED) 1390 - 25.7W 1670 - 32.2W 1950 - 38.5W 2230 - 45W 2510 - 53W	
	TOTAL WATTAGE AND LUMEN OUTPUT WILL VARY SLIGHTLY DEPENDING ON CONSTANT CURRENT OUTPUT.	
DIMMING OPTIONS	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100% 110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100%	
	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.	
	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	
DRIVER SIZE	220-240V PHASE ALL LP - L140 X W40 X H23 / L5.5" X W1.6" X H0.9" 220-240V DALI ALL LP - L97 X W43 X H30 / L4.8" X W1.7" / X H1.2" 110-120V PHASE / DALI 1390 / 1670 - L88 X W43 X H26.5 / L3.5" X W1.7" X H1" 1950 / 2230 / 2510 - L121 X W44 X H26.5 / L4.8" X W1.7" X H1" UP & DOWN LIGHTING IS INDIVIDUALLY ADDRESSABLE, 2X DRIVERS PER FIXTURE (CONTACT FOR ALTERNATE OPTIONS)	
LED LIFESPAN	50,000 HRS	
CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN PENDING CERTIFICATION	
IP RATING	IP20 - FOR INDOOR USE ONLY	

DIMENSIONS	VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*		
SKU CODES	EG. LP1950.TD.BR-AGE-R - LIMINAL 1950 PENDANT WITH TRIPLE DROPS, IN HAND RUBBED AGED BRASS FINISH LP.XXXX.TD.XX-XXX TRIPLE DROP LP.XXXX.DD.XX-XXX DOUBLE DROP LP.XXXX.XX.XX-XXX-R HAND RUBBED FINISH LP:1390.XX.XX-XXX L1390MM LP:1670.XX.XX-XXX L1670MM LP:1950.XX.XX-XXX L1950MM LP:2230.XX.XX-XXX L2230MM LP:2510.XX.XX-XXX L2510MM		
FINISHES	ALUMINIUM (A)	CHAMPAGNE ANODISED (A-CHM) BLACK ANODISED (A-BLK) HAND RUBBED ALUMINIUM (AL-NAT-R)	
	BRASS (BR)	BRUSHED BRASS (BR-NAT) HAND RUBBED BRASS (BR-NAT-R) BRUSHED AGED BRASS (BR-AGE) HAND RUBBED AGED BRASS (BR-AGE-R) BRUSHED BRONZED (BR-BRZ) HAND RUBBED BRONZED (BR-BRZ-R) BRUSHED BLACKENED (BR-BLK) HAND RUBBED BLACKENED (BR-BLK-R)	
PRODUCT WEIGHT	LP:1390	A - 6KG / 13.2LB	BR - 14.6KG / 32.2LB
	LP:1670	A - 7.1KG / 15.7LB	BR - 16.7KG / 36.8LB
	LP:1950	A - 8KG / 17.6LB	BR - 19.2KG / 42.3LB
	LP:2230	A - 8.9KG / 19.6LB	BR - 21.1KG / 46.5LB
	LP:2510	A - 9.8KG / 21.6LB	BR - 23.3KG / 51.4LB
PACKAGING DIMENSIONS	LP:1390 / 1670	L1710 X W220 X H140	
	LP:1950 / 2230	L2270 X W220 X H140	
	LP:2510	L2550 X W220 X H140	
PACKAGING WEIGHT	LP:1390	A - 9KG / 19.8LB	BR - 17.6KG / 38.8LB
	LP:1670	A - 10.6KG / 23.4LB	BR - 20.2KG / 44.5LB
	LP:1950	A - 12KG / 26.5LB	BR - 23.2KG / 51.1LB
	LP:2230	A - 13.4KG / 29.5LB	BR - 25.6KG / 56.4LB
	LP:2510	A - 14.8KG / 32.6LB	BR - 28.3KG / 62.4LB

DIMENSIONS

LP:1390.TD L1390 W48 H64 / L54.7" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8"	LP:1390.DD L1390 W48 H64 / L54.7" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8" CEILING CANOPY SPACING - 700MM / 27.56"
LP:1670.TD L1670 W48 H64 / L65.7" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8"	LP:1670.DD L1670 W48 H64 / L65.7" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8" CEILING CANOPY SPACING - 980MM / 38.58"
LP:1950.TD L1950 W48 H64 / L76.8" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8"	LP:1950.DD L1950 W48 H64 / L76.8" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8" CEILING CANOPY SPACING - 1260MM / 49.61"
LP:2230.TD L2230 W48 H64 / L87.8" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8"	LP:2230.DD L2230 W48 H64 / L87.8" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8" CEILING CANOPY SPACING - 1540MM / 60.63"
LP:2510.TD L2510 W48 H64 / L98.8" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8"	LP:2510.DD L2510 W48 H64 / L98.8" W1.9" H2.5" MIN DROP HEIGHT - H300 / 11.8" CEILING CANOPY SPACING - 1820MM / 71.65"

*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION, TOLERANCE IS +/- 25MM
*POWER ACCESS POINT REQUIRED AT CENTRE CEILING CANOPY FOR TRIPLE DROP, OR FROM ONE CANOPY FOR DOUBLE DROP.

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED THE LIMINAL FIXED CANOPY (TRIPLE DROP) / SLIM CANOPY (DOUBLE DROP) WILL BE SUPPLIED.

*FOR TRIPLE DROP PITCHED CEILING REQUIREMEN, PLEASE CONTACT THE STUDIO

TRIPLE DROP



LIMINAL
FIXED CANOPY
CAN.LP.X-XXX

280 X 130 X 12MM / 11" X 5.1" X 0.5"

DRIVER HOUSED IN CEILING



PUCK*
Ø14MM FIXED CANOPY
CAN.PK.F14.X-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING

*NOT AVAILABLE FOR US/CAN ORDERS



RECTANGULAR
FIXED CANOPY
CAN.LP.REC.X-XXX

420 X 170 X 37MM / 16.5" X 6.7" X 1.5"

DRIVER HOUSED IN CANOPY

DOUBLE DROP



SLIM
Ø14MM FIXED CANOPY
CAN.SL.F14.X-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING



SLIM
Ø14MM FIXED SWIVEL CANOPY
CAN.SL.F14.SW.X-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING



PUCK*
Ø14MM FIXED CANOPY
CAN.PK.F14.X-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING

*US/CAN ORDERS TO BE
INSTALLED WITH SUPPLIED
JUNCTION BOX RENDER
MOUNTING PLATE



PUCK*
Ø14MM FIXED SWIVEL CANOPY
CAN.PK.F14.SW.X-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING

*US/CAN ORDERS TO BE
INSTALLED WITH SUPPLIED
JUNCTION BOX RENDER
MOUNTING PLATE

TECHNICAL

MATERIAL	TREATED BRASS OR TREATED / ANODISED ALUMINIUM
CANOPY FINISH	CANOPY FINISH TO MATCH FRAME
SKU CODES	EG. CAN.LP.BR-NAT = LIMINAL CANOPY IN BRUSHED BRASS FINISH